



## AK-E107 Series EPON SFU

### General Description

AK-E107 series is a new EPON ONU production of ANYK Technology's passive optical network terminal series. It provides GE interface, one optical interface, it's very suitable for home and small business users, can satisfy the FTTH high-speed data transmission.

### Outline



### Key Features

- ☑ It takes the PTMP (point to multipoint) network topology, effectively collects and converges scattered Ethernet services, and provides the 10/100/1000M Ethernet standard RJ45 interface, smoothly interconnects with existing networks;
- ☑ The Dynamic Bandwidth Allocation (DBA) mechanism enables all users to share the bandwidth reasonably, guaranteeing a reliable QoS;
- ☑ Supports IGMP multicast, effective use of broadband;
- ☑ Supports multicast VLAN;
- ☑ Supports China Telecom CTC protocol;
- ☑ Full management through an Operation Administration Maintenance (OAM) protocol based on IEEE802.3ah, including configuration, alarm, performance monitoring, fault isolation and security management, etc. It supports remote management through OLT and local console management as well;
- ☑ Supports FEC and DBA;
- ☑ Supports IEEE802.1Q VLAN protocol;
- ☑ Supports IEEE 802.1p protocol;
- ☑ Supports remote loopback and network status diagnosis;
- ☑ Supports flow statistics;
- ☑ Supports storm control.

### Technical Parameters

<b>Model</b>	AK-E107
<b>User interface</b>	1 10/100/1000M RJ45 port.



<b>PON</b>	Transmission speed: upstream/downstream symmetrical 1Gbps Network coverage radius: 20KM Optical receive sensitivity: $\geq -27\text{dBm}$ Luminous power: $< 0\text{dBm}$ Security: ONU authentication mechanism
<b>Protocol</b>	Compliant with IEEE 802.3ah YD/T 1475-2006 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IEEE 802.1w, RSTP IEEE 802.3ad (LACP) Ethernet-II, Ethernet-SNAP
<b>VLAN</b>	Port-based VLAN GVRP IEEE 802.1Q VLAN
<b>QOS</b>	Backpressure flow control(half-duplex) IEEE 802.3x flow control(full-duplex) Prevent Head Of Line IEEE 802.1p, CoS WR,SP and FIFO queue scheduling algorithm Port rate limit
<b>Safety</b>	IEEE 802.1x, access control based upon Port; support local and remote RADIUS. CHAP,EAP certification; Storm control, port protection,
<b>Management</b>	Various management modes such as Web, TELNET Debug function.
<b>Environment</b>	Operating temperature: $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ ; Operating humidity: $10\% \sim 85\%$ non-condensing
	Storage temperature: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$ ; Storage humidity: $5\% \sim 95\%$ non-condensing
<b>Power supply</b>	110~240VAC 12V/0.5A DC
<b>Power Consumption</b>	6W

## Volume and Weight

ONU Dimension				
Type	Length	Width	Height	Volume
AK-E107 Series	130mm	100mm	28mm	$\text{mm}^3$
ONU Packing Dimension				
Type	Length	Width	Height	Volume
AK-E107 Series	239mm	125mm	54mm	$\text{mm}^3$
ONU Weight				
Type	Gross Weight		Net Weight	
AK-E107 Series	0.3kg		0.15kg	

## Order Information

Model	Description
AK-E107	EPON ONU, One 10/100/1000M RJ45 port. Color: White