



AK-G211 GPON HGU

General Description

AK-G211 is a new GPON ONU production of ANYK Technology's passive optical network terminal series. It provides 1GE RJ45 port, 1FE RJ45 port, 1 RJ11 VoIP, 1 USB interface and 1 optical interface, it's very suitable for home and small business users, can satisfy the FTTH high-speed data transmission.

Outline



Key Features

- ☑ Integrated GPON interface, to meet the ITU-T G.984 specification;
- ☑ It takes the PTMP (point to multipoint) network topology, effectively collects and converges scattered Ethernet services, and provides the 10/100/1000M Ethernet standard RJ45 interface, smoothly interconnects with existing networks;
- ☑ The Dynamic Bandwidth Allocation (DBA) mechanism enables all users to share the bandwidth reasonably, guaranteeing a reliable QoS;
- ☑ Supports IGMP multicast, effective use of broadband;
- ☑ Supports multicast VLAN;
- ☑ Supports China Telecom CTC protocol;
- ☑ Full management through an Operation Administration Maintenance (OAM) protocol based on IEEE802.3ah, including configuration, alarm, performance monitoring, fault isolation and security management, etc. It supports remote management through OLT and local console management as well;
- ☑ Supports FEC and DBA;
- ☑ Supports IEEE802.1Q VLAN protocol;
- ☑ Supports IEEE 802.1p protocol;
- ☑ Supports remote loopback and network status diagnosis;



- ☑ Supports flow statistics;
- ☑ Supports storm control.

Technical Parameters

Model	AK-G211
User interface	1 GE, 1 FE, 1 RJ11 VoIP,1 USB.
PON	Transmission speed :upstream1.25Gbps/downstream2.5Gbps Network coverage radius: 20KM Optical receive sensitivity: $\geq -28\text{dBm}$ Luminous power: $< 0\text{dBm}$ Security: ONU authentication mechanism
Protocol	Compliant with IEEE 802.3ah YD/T 1475-2006 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IEEE 802.1w, RSTP IEEE 802.3ad (LACP) Ethernet-II, Ethernet-SNAP
USB	1 USB 2.0 HOST interface which can provide 5V voltage with max current 1A Support external storage device
Voice	Support SIP protocol Support multi voice encoding format: PCMU, PCMA, G.722, G.723, G.726-32, G.729 Support voice value-added services: call forwarding, call waiting, call identification, abbreviated dialing, hot line service, do not disturb service, alarm clock, call barring, three-way calling
VLAN	Port-based VLAN GVRP IEEE 802.1Q VLAN
QOS	Backpressure flow control(half-duplex) IEEE 802.3x flow control(full-duplex) Prevent Head Of Line IEEE 802.1p, CoS WR,SP and FIFO queue scheduling algorithm Port rate limit
Safety	IEEE 802.1x, access control based upon Port; support local and remote RADIUS. CHAP,EAP certification; Storm control, port protection,
Management	Various management modes such as Web, TELNET Debug function.
Environment	Operating temperature: $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$; Operating humidity: $10\% \sim 85\%$ non-condensing
	Storage temperature: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$; Storage humidity: $5\% \sim 95\%$ non-condensing
Power supply	110~240VAC 12V/1A DC
Power Consumption	12W



Dimension and Weight

AK-G211	Device	Packing
Dimension L*W*H/mm	117*45*172	239*125*54
Weight/kg	0.25	0.42

Order Information

Model	Description
AK-G211	GPON HGU, 1 * FE RJ45, 1 * GE RJ45, 1 * RJ11 VOIP, 1 USB, black& red